



### General

The BTM 09 is a full-graphics HMI especially designed for tasks such as controlling, entering parameters and operating in the harsh environment of vehicles and self-propelled machines. It complies with the applicable safety requirements as to ambient temperatures, tightness, shock, vibration and electromagnetic compatibility (EMC). It can also be installed outside the driver's cab. The totally-enclosed body of the BTM 09V is made of cast aluminum and equipped with a Goretex® membrane for pressure compensation. This way, all sides of the enclosure meet IP65.

The keyboard has a "night design" to light the keys. The display brightness and key lighting can be adjusted in the application program according to the ambient brightness. If automatic brightness control is enabled, adaptation to the lighting conditions is automatically controlled by a light sensor. Keys are ergonomically arranged which offers the option to display a description of the related function on the screen.



On the rear of the device there are 2 waterproof plugs/sockets and the venting element to equalize pressure.

A CAN interface to ISO 11898 2.0B has been applied to the 5-pin M12 plug.

The power supply of the device has been applied to the 3-pin M8 plug.

All rights reserved.

Jetter AG reserve the right to make alterations to its products in the interest of technical progress. These alterations will not necessarily be documented in every single case.

This application note and the information contained herein have been compiled with due diligence. However, Jetter AG assume no liability for printing or other errors or damages arising from such errors.

The brand names and product names used in this document are trademarks or registered trademarks of the respective title owner.

Jetter AG  
 Graeterstrasse 2  
 71642 Ludwigsburg  
 Germany


Phone - Switchboard: ++49 7141/2550-0  
 Phone - Sales: ++49 7141/2550-530/-531  
 Phone - Technical Hotline: ++49 7141/2550-444

Fax: ++49 7141/2550-566  
 E-mail - Sales: sales@jetter.de  
 E-mail - Technical Hotline: hotline@jetter.de  
 Internet Address: http://www.jetter.de

## Technical Specifications


Display:	Color LCD flat screen, 5.7", 640 x 385 pixels
Operating voltage:	9 ... 32 VDC 1 A typical input current at 12 VDC 600 mA typical input current at 24 VDC
Connections:	5-pin male connector M12 - CAN interface 3-pin male connector M8 - operating voltage
Keyboard:	15 illuminated keys (night design)
Dimensions	200 x 137 x 60 mm (W x H x D)
Operating temperature:	-20 ... 60 °C
Storage temperature:	-30 ... 70 °C

## Contact Assignment



CAN interface (5-pin male connector M12)

- 1 Ground
- 2 -
- 3 -
- 4 CAN-H
- 5 CAN-L



Power supply (3-pin male connector M8)

- 1 + VDC
- 2 NC
- 3 GND

**Item No: C115**

Key Codes:



Cut-out:

