

## JetViewMobile M043 Display for mobile machinery

### Short description

The outstanding feature of the new monitor generation JVM-Mxxx is its brilliant displays of appealing design which are also readable in bright sunlight.

Coming as mere monitors of 4.3 to 10.1", the devices are low-size enough to be installed even in small spaces.

The corresponding high-performance ECU JCM-630 does not only establish all connections with the mobile machine, but it also provides two monitors with operating parameters by single-cable technology.

Thanks to its multi-kernel processors, its four CAN, LIN, Gbit Ethernet connections, and its eight camera inputs, the JCM-630 is fit for any kind of today's and tomorrow's operating philosophy.



### Features

- Brilliant displays readable in bright sunlight
- Slim, modern design
- Single-cable connection to JCM-630
- PCAP can be integrated
- Mounting: VESA/RAM, flush mounting


# JetViewMobile M043

## Technical Data

JVM-M043	
Display	10.1" TFT with LED backlight
Resolution	1280 x 800 pixels
Brightness	500 cd/m2( dimmable)
Viewing angle (h/v, u/d)	160°;160°
Contrast	500:1
Control elements	1; PCAP touchscreen (option) 4; Keys, backlit (option) 1; Push encoder, backlit (option)
Acoustic signaling	1; Buzzer 85 db (option)
Ports and interfaces	
- FPD-LINKII	1; Display, display power supply, CAN
- CAN	1; CANopen®; 125 kB/s to 1 MB/s
- External keyboard, push encoder, ...	10 ch.; Matrix keyboard, switches, push encoder (option)
Programming	Via JCM-630 series Graphics: JetViewSoft - Logics: IEC61131-3 STX
Operating voltage	DC 8 ... 32 V
Operating/storage temperature	-20 ... +65 °C/-30 ... +85 °C
Degree of protection	Flush mount model "open frame": IP23 front/IP20 rear Surface mount model: IP54 front/IP54 rear
Vibration	DIN EN 60068-2-64, Cat. 2
Shock	DIN EN 60068-2-64, 30g
Protection against polarity reversal	Yes

Further details and order information are available on request. Specifications are subject to change without notice. Errors and omissions excepted.

## Dimensional drawing



RAM Mount adapter not included in the scope of delivery.

